

DISCOVER THE FULL RANGE OF BATTERY DRIVEN BAHCO PRUNING AND LANDSCAPING TOOLS

PRUNING AND LANDSCAPING TOOLS



BCL21
Compact
Electric Secateurs



BCL22
Heavy Duty
Electric Secateurs



BCL111*
Hedge Trimmer



BCL115*
Telescopic
Hedge Trimmer



BCL121**
Brush Cutter



BCL131
Pruner



BCL132
Hand Held Pruner



BCL135
Telescopic
Pole Saw



BCL141
Soil Cultivator



BCL142A
Blower

* Delivered without blade

** Delivered without cutting head and cutting blade / wire

BATTERIES & COMPATIBILITIES



150Wh
BCL1B1

BCL21*



250Wh
BCL1B2

BCL21
BCL22**
BCL132
BCL135
BCL141



400Wh
BCL1B4

BCL111
BCL115
BCL131
BCL132
BCL135
BCL141



750Wh
BCL1B7

BCL111
BCL115
BCL131
BCL132
BCL135
BCL121
BCL141



1.000Wh
BCL1B10

BCL111
BCL115
BCL131
BCL132
BCL135
BCL121
BCL141
BCL142A

* BCL21 secateurs includes BCL1B1 battery in the set

** BCL22 secateurs includes BCL1B2 battery in the set



www.bahco.com

SNA Europe BCL15-FRE



BAHCO BLOWER POWER AND SILENCE



3 YEARS
WARRANTY

BCL142A

POWER AND SILENCE

A tool that is equally powerful, comfortable and quiet.

Designed to reduce the noise level without compromising the blowing power performance, the Bahco blower is the perfect tool to use near urban spaces, parks, schools and hospitals.



BAHCO Services

Bahco Services offers each customer guaranteed access to a package of services including a commercial department that offers advice on which tool best suits for the job as well as financing and leasing solution.

The Bahco network ensures local after sales service of the Bahco tools in order to maintain their performance.

Up to a full day's work	ONLY 2.55Kg	Can lift up to 1.78kg
--------------------------------	--------------------	------------------------------

Lifting power*	1,78 kg (boost) / 1,37 kg (speed 4)
Max. power	940 W
Heat engine equivalence	20 cm ³
Air flow rate**	920 m ³ /h (boost) / 810 m ³ /h (speed 4)
Air speed**	63 m/s (boost) / 55 m/s (speed 4)
Air speed with flat nozzle	69 m/s (boost) / 60 m/s (speed 4)
Noise level (LPA)***	79 dB(A)
Guaranteed sound level (LWA)***	92 dB(A)
Pressure level at 15 meters*	< 65 dB(A)
Vibration level (ah)**** - less than or equal to	< 2,5 m/s ² (0,5 actual)

* ANSI/OPEI B175.2-2012 norm

** With round nozzle 75mm

*** Values determined according to the acoustic measurement standards NF EN ISO 11203, NF EN ISO 3744 and NF EN ISO 4871

**** Vibration emission value following DIN EN 60745-1:2009 - uncertainty Kd = 1,5 m/s²

Offset suction inlet
Reduction of the noise level without compromising blowing power

Speed selector
allowing to select 5 different speed positions; adapt the speed of air to environment

Comfortable bi-material handle
with rubber grip

Progressive trigger

Hook for the carrying strap.
Can be placed on either side

Against TMS
tension myositis syndrome

Balanced forces
Blast pressure
Suction pressure

OFFSET SUCTION INLET
Perfect weight / balance ratio
A blower pushes air toward the leaves and tends to suck the collection nozzle to the ground. On a straight blower this phenomenon is aggravated. Thanks to the curved design of the Bahco blower the tools stays perfectly balanced.

Profiled nozzle

Intake grid
Increases the efficiency of the blower

Long lasting axial turbine
Engine surrounded by a magnesium casing > Hermetic IP54 level all mechanical parts are protected from dust and splashing water

Accessories and Consumables
For a wide variety of applications

BCL142T1 Round blowing nozzle

Internal diameter: Ø 65 mm
Length : 57 cm

BCL142T2 Scratching nozzle

Internal diameter: Ø 65 mm
Length: 57 cm

BCL142T3 Round blowing nozzle

Internal diameter: Ø 75 mm
Length : 57 cm
Sold as standard

BCL142T31 Flat blowing nozzle

Length: 77 cm
Sold as standard

Carrying strap
For more comfort and enlighten even more the weight. Kit containing the strap and the hook.
Sold as standard

Blower holder hook
Attach to the battery belt it enable the user to have it hands free.
Sold as standard